


TECHNICAL DATASHEET

APPLICATIONS



SURFACE	Natural
BASE	Coloured paper
DECORATION BY	Foil stamping, silk screen, offset and digital printing. Subject to test before using. Please consult us.
TESTS	Lightfastness: 3- 5 dependant on colour - ISO 105-BO2 Burst: 350 Minimum - ISO 2758 Cobb: 25 Target - ISO 535:2014 Smoothness: 860 Target - ISO8791-2:2013
MIN. QUANTITY SPECIALS	3 tonnes special colour, 2 tonnes for standard stock colour in special size. Special substance (g/m²): please consult us.
PRODUCTION TIME	4-6 weeks. Subject to seasonal variations.
ROLL WIDTH	1020 mm
ROLL LENGTH	1000 m
SHEETS	1020 × 760 mm SG, 640 × 970 mm LG
NET WEIGHT	~120 g/m²
THICKNESS	~0.16 mm
TYPE OF PACKAGING	200 sheet packets: paper wrapped, 1000 m rolls: film wrapped
SIZES OF PACKAGING	200 sheets 1020 × 760 mm: 106 × 78 × 5 cm 200 sheet 640 × 970 mm: 106 × 69 × 5 cm 1000 m roll : 102 × 47 × 47 cm
INNER CORE Ø	7.6 cm
GROSS WEIGHT	200 sheet 1020 × 760 mm: ~20 kg 200 sheet 640 × 970 mm: ~16 kg 1000 m roll: ~130 kg
NET WEIGHT	200 sheet 1020 × 760 mm: ~18 kg 200 sheet 640 × 970 mm: ~15kg 1000 m roll: ~120 kg
CUSTOMS DECLARATION	Printing paper
TARIFF NUMBER	4804.3980 (Switzerland) / 4804 3980 000 (European Community)
ENVIRONMENTAL DATA	   

